

**NATURAL RESOURCES CONSERVATION SERVICE  
CONSERVATION PRACTICE STANDARD**

**MULCHING**

**(AC.)**

**CODE 484**

**DEFINITION**

Applying plant residues or other suitable materials produced off site, to the land surface.

**PURPOSE**

This practice supports one or more of the following purposes:

- Conserve soil moisture – Resource concern (INSUFFICIENT WATER – Inefficient moisture management).
- Reduce energy use associated with irrigation – Resource concern (INEFFICIENT ENERGY USE – Farming/ranching practices and field operations and INSUFFICIENT WATER – Inefficient moisture management).
- Provide erosion control – Resource concern (SOIL EROSION– Excessive bank erosion from streams shorelines or water conveyance channels, and/or SOIL EROSION – Concentrated flow erosion, and/or SOIL EROSION - Sheet, rill, & wind erosion).
- Facilitate the establishment of vegetative cover – Resource concern (DEGRADED PLANT CONDITION – Undesirable plant productivity and health).
- Improve soil health – Resource concern (SOIL QUALITY DEGRADATION – Organic matter depletion).
- Reduce airborne particulates – Resource concern (AIR QUALITY IMPACTS - Emissions of Particulate Matter - PM - and PM Precursors).

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to all lands where mulches are needed. This practice may be used alone or in combination with other practices.

**CRITERIA**

**General Criteria Applicable to All Purposes**

The selection of mulching materials will depend primarily on the purpose(s) for the mulch application site conditions and the material's availability. Mulch materials shall consist of natural and/or artificial materials that are of sufficient dimension (depth or thickness) and durability to achieve the intended purpose for the required time period.

Prior to mulching, the soil surface shall be prepared in order to achieve the desired purpose.

The mulch material shall be evenly applied and, if necessary, anchored to the soil. Tackifiers, emulsions, pinning, netting, crimping or other acceptable methods of anchoring will be used if needed to hold the mulch in place for specified periods.

In cases where excessive furrow erosion may occur due to concentrated flows from plastic mulches, appropriate measures will be taken to protect the furrows.

As a minimum, manufactured mulches shall be applied according to the manufacturer's specifications.

Mulch material needs to be of a quality to meet the intended purpose.

**Additional Criteria to Conserve Soil Moisture and/or Reduce Energy Use Associated with Irrigation**

Mulch materials applied to the soil surface shall provide at least 60 percent surface cover to reduce potential evaporation.

**Additional Criteria to Provide Erosion Control and to Reduce Airborne Particulates**

When mulching with cereal grain straw or grass hay, apply at a rate to achieve a minimum 70 percent ground cover. See the Michigan NRCS Electronic Field Office Technical Guide eFOTG Revised Universal Soil Loss Equation (RUSLE2). Mulch designs can be evaluated for water erosion prediction under the Management Folder, Section d., Construction Site Template. Select the Vegetation Permanent Cover Not Harvested Folder to determine the erosion rate as mulched.

When mulching with wood products such as wood chips, bark, or shavings or other wood materials, apply a minimum 2-inch thickness comprised of particles that remain in place during heavy rainfall and or strong wind events.

When mulching with gravel or other inorganic material apply a minimum 2 inch thickness consisting of pieces 0.75 to 2 inches in diameter.

**Additional Criteria to Establish Vegetative Cover**

Mulch shall be applied at a rate that achieves a minimum of 70 percent ground cover to provide protection from erosion and runoff and yet allow adequate light and air penetration to the seedbed to ensure proper germination and emergence.

**Additional Criteria to Improve Soil Health**

Use plant-based mulching materials of suitable quantity and quality to add organic matter, provide food and shelter for soil biota, and protect the soil surface from raindrop impact and crusting, while allowing for adequate soil aeration.

Apply mulch materials with a carbon to nitrogen ratio (C: N) less than 30 to 1 so that soil nitrogen is not immobilized by soil biota. Do not apply mulch with C: N less than 20:1 to an area of designed flow in watercourses.

Evaluate the system using the current approved soil conditioning index (SCI) procedure so that the analysis is zero or higher.

**CONSIDERATIONS**

Evaluate the effects of mulching on evaporation, infiltration, and runoff. Mulch material may affect microbial activity in the soil surface, increase infiltration, and decrease runoff, erosion, and evaporation. The temperature of the surface runoff may also be lowered.

Conserve soil moisture by applying mulch material prior to moisture loss. Prior to mulching, ensure soil under shallow rooted crops is moist, as these crops require a constant supply of moisture.

Mulch materials with a high water holding capacity and/or high impermeability to water droplets may adversely affect the water needs of plants.

Fine textured mulches (e.g. rice hulls) which allow less oxygen penetration than coarser materials should be no thicker than 2 inches.

Avoid excessively thick or tightly packed mulches that can result in soggy, anaerobic conditions at the soil surface during wet weather; or prevent rainfall or overhead irrigation from reaching the soil during times of moisture deficit.

Organic materials with C: N ratios of less than 20:1 will release nitrate-nitrogen which could cause water quality impairments.

Finely-divided plant residues (e.g., sawdust) and those rich in soluble carbohydrates (e.g., fresh green-chopped sorghum-Sudan grass, corn, or other grasses) that have a C: N ratio greater than 30 can tie up soil N and necessitate supplemental N applications on crops. Coarser materials such as grain straw and chipped brush usually do not reduce crop-available soil N levels unless and until they are incorporated into the soil by tillage or cultivation.

Mulching may also provide habitat for beneficial insect and provide pest suppression.

Use mulch of sufficient ground cover, and suitable thickness and texture to provide habitat for ground beetles, spiders, and other predators of weed seeds and crop pests. Select crops to be mulched, mulching materials, and rates of

application that do not contribute to pest problems. Avoid excessively thick or tightly-packed mulches, which can interfere with the movement of ground beetles and other beneficial organisms, and may increase the incidence of crop pests and diseases.

During the period when weed seed predation is desired and predators are most active, avoid Light-reflecting mulches such as white or aluminized plastic film or bright straw can repel some pests.

Clear and infra-red transmissible (IRT) plastics have the greatest warming potential. They are transparent to incoming radiation and trap the longer wavelengths radiating from the soil. Black mulches are limited to warming soils by conduction only and are less effective.

Clear mulches allow profuse weed growth and may negate the benefits of soil warming. Black mulches provide effective weed control. Wavelength selective (IRT) plastic provides the soil warming characteristics of clear mulch with the weed control ability of black mulch.

Select mulching materials and methods that are compatible with the crop and site. Consider potential beneficial or detrimental effects of mulching materials on the biotic community surrounding the crop, including beneficial soil micro- and macro-organisms, as well as plant pathogens and plant pests. These effects are specific to site, mulch, and crop, and may include enhanced soil microbial activity, increased or reduced levels of crop diseases, and toxic (allopathic) activity against the crop, weeds, or other beneficial or pest organisms.

Keep mulch 3 to 6 inches away from plant stems and crowns to prevent disease and pest problems. Additional weed control may be needed around the plant base area.

Deep mulch provides nesting habitat for ground-burrowing rodents that can chew extensively on tree trunks and/or tree roots. Light mulch applied after the first cold weather may prevent rodents from nesting.

Some mulch material may adversely affect aquatic environments through changes in water chemistry or as waterborne debris. Consider placing mulch in locations that minimizes these risks.

Consider potential effects of soil physical and chemical properties. Refer to soil survey data as a preliminary planning tool for assessment of areas. Consult the Web Soil Survey at: <http://websoilsurvey.nrcs.usda.gov/app/> to obtain Soil Properties and Qualities information.

For all organic or transitioning to organic operations, follow all National Organic Program (NOP) rules.

## PLANS AND SPECIFICATIONS

Specifications shall be prepared for each site and purpose and recorded in specification or job sheets with the approved implementation requirements documentation.

Documentation shall include:

- Purpose of the Mulch
- Type of mulch material used
- The percent cover and/or thickness of mulch material
- Timing of application
- Site preparation
- Listing of netting, Tackifiers, or method of anchoring, and
- Operation and maintenance.

## OPERATION AND MAINTENANCE

Mulched areas will be periodically inspected, and mulch shall be reinstalled or repaired as needed to accomplish the intended purpose.

Evaluate the effectiveness of the mulch (application, amount of cover provided, durability, etc.) and adjust the management or type of mulch to better meet the intended purpose(s).

Removal or incorporation of mulch materials shall be consistent with the intended purpose and site conditions.

Operation of equipment near and on the site shall not compromise the intended purpose of the mulch.

Prevent or repair any fire damage to the mulch material.

Properly collect and dispose of artificial mulch material after intended use.

Monitor and control undesirable weeds in mulched areas.

## REFERENCES

Agriculture and Agra-Food Canada. 2000. Plastic mulches for commercial vegetable production. Canada-Saskatchewan Irrigation Diversification Centre. Outlook, Saskatchewan.

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool, and D.C. Yoder, Coordinators. 1997. Predicting soil erosion by water: A guide to conservation planning with the Revised

Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture, Agriculture Handbook No. 703.

Shaffer, M.J., and W.E. Larson (Ed.). 1987. NTRM, a soil-crop simulation model for nitrogen, tillage and crop residue management. USDA Conservation Res. Rep. 34-1. USDA-ARS.

Toy, T.J., and G.R. Foster. (Ed.) 1998. Guidelines for the use of the Revised Universal Soil Loss Equation (RUSLE) Version 1.06 on mined lands, construction sites, and reclaimed lands. USDI, OSMR.

USDA, NRCS. 2011. National Agronomy Manual. 190-V, 4<sup>th</sup> Ed. Washington, D.C